

11/16/00
JC815 U.S. PTO
09/714340

11/17/00

Case Docket No. ITW-12833

A

Express Mail No.: EL686797719US

Date of Deposit: 16 November 2000

ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Transmitted herewith for filing is the patent application of

Inventors: William N. WEAVER et al.

For: SYSTEM AND APPARATUS FOR PACKAGING CONTAINERS

Enclosed are:


- ☒ Seventeen (17) pages of specification, five (5) pages of claims (Claims 1-18), one (1) page of Abstract, and seven (7) sheets of drawings (Figs. 1-11).
- ☒ Executed combined Oath or Declaration, Power of Attorney and Petition (3 pages).
- ☒ Certificate of Mailing by Express Mail (2 pages).
- ☒ Recordation Form Cover Sheet, together with executed Assignment Document (3 pages) and a check in the amount of \$40.00 to cover the recordal of Assignment fee.
- ☒ Return Receipt Postcard.

The filing fee has been calculated as shown below:

	COL. 1	COL. 2	SMALL ENTITY		LARGE ENTITY		
FOR:	NO. FILED	NO. EXTRA	RATE	FEE	OR	RATE	FEE
BASIC FEE				\$355	OR		\$710
TOTAL CLAIMS	18 less 20	0	X 09 =		OR	X 18 =	0
INDEPENDENT CLAIMS	3 less 3	0	X 40 =		OR	X 80 =	0
MULTIPLE DEPENDENT CLAIMS PRESENTED			+135=		OR	+270 =	
* IF THE DIFFERENCE IN COL. 1 IS LESS THAN ZERO, ENTER "0" IN COL. 2			TOTAL		OR	TOTAL	710

- ☒ A check in the amount of \$710.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 19-3550. A duplicate copy of this sheet is enclosed.
 - ☒ Any additional filing fees required under 37 CFR 1.16.
 - ☐ Any patent application processing fees under 37 CFR 1.17.

Pauley Petersen Kinne & Fejer
2800 W. Higgins Road, Suite 365
Hoffman Estates, Illinois 60195
Phone (847) 490-1400
Fax (847) 490-1403


Kevin D. Erickson
Registration No. 38,736

P200/14

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: William N. WEAVER
Robert E. UNGAR
Lonnie R. SEYMOUR

Title: SYSTEM AND APPARATUS FOR PACKAGING
CONTAINERS

Express Mail No.: EL686797719US

Date of Deposit: 16 November 2000



CERTIFICATE OF MAILING BY EXPRESS MAIL

Box PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

I hereby certify that the subject patent application is being deposited with the United States Postal Service as Express Mail Post Office to Addressee No. EL686797719US, on 16 November 2000, and is addressed to Box PATENT APPLICATION, Assistant Commissioner for Patents, Washington, D.C. 20231, together with the items listed below.

- Transmittal Letter, in duplicate
- Seventeen (17) pages of specification, five (5) pages of claims (Claims 1-18), one (1) page of Abstract, and seven (7) sheets of drawings (Figs. 1-11)

[illegible]

- Respectfully submitted,

Kevin D. Erickson
Regis. No. 38,736

ITW-12833

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT**

INVENTORS: William N. WEAVER
Robert UNGAR
Lonnie R. SEYMOUR

TITLE: **SYSTEM AND APPARATUS FOR PACKAGING
CONTAINERS**

ATTORNEYS: Kevin D. Erickson
Pauley Petersen Kinne & Fejer
2800 W. Higgins Road
Suite 365
Hoffman Estates, Illinois 60195
(847) 490-1400

EXPRESS MAIL NO.: EL686797719US

MAILED: 16 November 2000

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to a container carrier applying system and apparatus for unitizing a plurality of containers.

Description of Prior Art

Container carriers connect two or more containers into a sturdy unitized package of containers. Carriers are generally planar arrays of rings, sometimes referred to as "six-pack carriers," typically formed from a thermoplastic sheet material. Carriers are applied to containers of various sizes and shapes. One important consideration in the design of a carrier is the adaptability of the carrier to such sizes and shapes. A cost-effective carrier is capable of application to a wide range of container sizes, specifically a wide range of container diameters.

Prior art multi-packaging devices and methods generally require several different versions or configurations of applying machines and/or carriers to accommodate different diameters of containers. Typically, a single design carrier and a single design applying machine can accommodate a range of container diameters of approximately 0.200 inches.

Applying machines are an additional limitation on the range of container diameters that can be effectively packaged by a single system. As described above, applying machines are limited in the range of container diameters that they can accommodate. A major reason for this limitation is that the carrier-engaging components

of an applying machine require a constant longitudinal distance between apertures of the carrier, also called "pitch," and/or a constant transverse distance between the apertures of the container carriers. In prior art systems, containers having different diameters required container carriers having different pitches. As a result, different applying machines were required to accommodate and apply container carriers having different pitches. Therefore, under the prior art, several carriers and several applying machines were required to apply carriers to uniform groups of containers having different diameters.

For example, current systems require a specific carrier and specific applying machine for containers having diameters ranging between 2.4 and 2.6 inches. A second specific carrier and a second specific applying machine are necessary for containers having diameters ranging between 2.6 and 2.8 inches. Finally, a third specific carrier and a third specific applying machine are necessary to accommodate container diameters up to 3.0 inches. Maintaining different applying machines for use in connection such a wide range of containers is both expensive and space intensive for a bottling facility.

SUMMARY OF THE INVENTION

It is one object of this invention to provide a system for unitizing a plurality of containers having a range of possible container diameters.

It is another object of this invention to provide a system for unitizing a plurality of containers wherein a longitudinal pitch of a carrier is greater than a container

pitch between adjacent containers in a resulting package.

A system for packaging multiple containers includes a carrier that moves through an applying machine having a drum. The carrier is positioned around a perimeter of the drum, and rotates onto uniform groups of containers having a first diameter. The containers are assembled and unitized in a single package. After a brief set-up period, a uniform group of containers having a second diameter may be packaged with the system according to this invention. A modified carrier having a different transverse width but an identical pitch is used to package the group of containers having the second diameter.

The carrier comprises a flexible plastic sheet formed with a plurality of elongated apertures aligned in transverse ranks and at least two longitudinal rows. Additionally, the carrier is formed with a plurality of relief holes positioned between adjacent longitudinal rows of the elongated apertures. Longitudinal extremities of the relief holes overlap end portions of adjacent elongated apertures in the longitudinal direction. With this overlapping configuration, the carrier avoids high stress regions that may otherwise develop in a carrier having such elongated apertures.

Each configuration of the carrier accommodates a group of like-sized containers having a uniform diameter within a limited range of diameters. The carrier is preferably reconfigured, by widening the carrier in the transverse direction and maintaining a constant pitch, for groups of container diameters outside of the limited range.

The carrier includes a longitudinal pitch between adjacent elongated apertures that has a first length prior to application to containers. Subsequent to application to a plurality of containers, a container pitch between adjacent containers in the package is a second length, shorter than the first length. Therefore, the maximum diameter of the containers and/or the spacing between adjacent containers prior to application of the carrier does not affect the relationship between the first length and the second length. The resulting second length (container pitch) after application of the carrier to the containers is always shorter than, or equal to, the first length (longitudinal pitch) of the carrier prior to application of the carrier to the containers.

The carrier is spooled through the applying machine and around the drum mentioned above. A plurality of jaw pairs are equally spaced around a perimeter of the drum. Each jaw pair comprises at least a moveable jaw and a fixed jaw. Each jaw pair is movable between a closed position and an open position along an axis parallel to the axis of the drum.

The carrier is fed onto the drum so that initially the jaw pairs are in the closed position and each jaw pair grips the carrier through a transverse pair of elongated apertures in the carrier. The circumferential spacing between adjacent jaw pairs is preferably approximately equal to the pitch of the carrier. The spacing between the moveable jaw and the fixed jaw in the closed position is preferably slightly less than the width between transverse pairs of elongated apertures.

The drum also includes an adjustment means for adjusting a distance

between the moveable jaw and the fixed jaw of each jaw pair in the closed position. Preferably, the adjustment means simultaneously adjusts each fixed jaw of each jaw pair.

The adjustment means preferably comprises a stationary hub journaled with respect to an adjustable hub, so that the adjustable hub is slidably connected with respect to the stationary hub. A center hub assembly together with several adjuster guide assemblies are positioned between the stationary hub and the adjustable hub so that the drum is quickly and easily adjustable between applications to containers having different diameters.

If a group of containers having a different diameter is packaged, the adjustment means is adjusted so that the jaw pairs can engage a carrier having a different width but a common pitch from the prior carrier. If a smaller diameter container is packaged, usually a smaller width carrier is required so the adjustable hub is moved inward with respect to the stationary hub. The distance between the moveable jaw and the fixed jaw in the closed position is thereby reduced and the smaller carrier is engaged with the jaw pairs for application to the smaller diameter containers. If a container having a larger diameter is packaged, the adjustable hub is moved outward with respect to the stationary hub and the distance between the moveable jaw and the fixed jaw in the closed position is expanded.

BRIEF DESCRIPTION OF THE DRAWINGS

The above-mentioned and other features and objects of this invention will be better understood from the following detailed description taken in conjunction with the

drawings wherein:

Fig. 1 is a diagrammatic side view of a prior art applying machine for packaging containers;

Fig. 2 is a diagrammatic side view of an applying machine for packaging multiple containers, according to one preferred embodiment of this invention;

Fig. 3 is a diagrammatic top view of a carrier according to one preferred embodiment of this invention;

Fig. 4 is a diagrammatic top view of a carrier according to another preferred embodiment of this invention;

Fig. 5 is a side view of a drum according to one preferred embodiment of this invention;

Fig. 6 is a front cross-sectional view of the drum shown in Fig. 5 further showing the additional detail of jaw pairs;

Fig. 7 is a diagrammatic perspective view of a carrier moving through a drum according to one preferred embodiment of this invention;

Fig. 8 is a top view of the jaw pairs in a closed position according to one preferred embodiment of this invention;

Fig. 9 is a side view of the jaw pairs shown in Fig. 8 extended in an open position;

Fig. 10 is a side view of a carrier according to one preferred embodiment of this invention; and

Fig. 11 is a side view of a package according to one preferred embodiment of this invention.

DESCRIPTION OF PREFERRED EMBODIMENTS

Fig. 1 shows a prior art system for packaging containers. As shown in Fig. 1, the prior art system comprises carrier 10' that moves through applying machine 30' around drum 40' and onto containers 5 to create assembled package 15. As shown in Fig. 1, containers 5 are generally of uniform size and diameter throughout the packaging process. A uniform group of containers 5 having a second diameter typically requires a separately configured carrier 10' as well as a separate applying machine 30" (not shown).

Fig. 2 shows a system for packaging multiple containers according to one preferred embodiment of this invention. As shown, carrier 10 moves through applying machine 30 and through guide plate 32 to drum 40. Drum 40, having carrier 10 positioned around perimeter, rotates over and onto uniform groups of containers 5 having a first diameter. Containers 5 are assembled and unitized in a single package 15. According to one preferred embodiment of this invention, if a uniform group of like-sized containers 5 having a second diameter requires packaging, a separately configured carrier 10 having an identical pitch as carrier 10 for containers having the first diameter is positioned in applying machine 30 after adjustment of drum 40, as described below.

Therefore, the system for packaging multiple containers 5 according to this invention permits the use of a single applying machine 30 in combination with a variety

of diameters of containers 5 and therefore sizes of carriers 10. Applying machines 30 are typically fifteen or more feet long and six or more feet wide, therefore a reduction in the number of applying machines 30 required in a packaging plant significantly reduces the required working floor space within the plant.

Carrier 10 preferably moves through applying machine 30 from reel 33 ultimately to packages 15, each package 15 containing a plurality of uniform containers 5. A typical configuration for package 15 is a "six-pack" containing two longitudinal rows of containers 5 in three transverse ranks. Carriers 10 are typically connected end-to-end in a continuous planar sheet which is preferably rolled onto reels 33 for spooling onto applying machine 30.

Carrier 10 is preferably constructed from a flexible plastic sheet, such as low-density polyethylene. As shown in Figs. 3 and 4, the flexible plastic sheet is punched or otherwise formed into a plurality of elongated apertures 20 aligned in transverse ranks and at least two longitudinal rows to form a continuous sheet of carriers 10. Elongated apertures 20 are preferably oriented in a longitudinal direction with respect to carrier 10. In one preferred embodiment of this invention, elongated apertures 20 are approximately four to six times longer than wide. Such an elongated configuration permits carrier 10 to accommodate several diameters of containers 5 without varying pitch 18 of carrier, i.e. a longitudinal center-to-center distance between adjacent elongated apertures 20, for example a 3" pitch 18 in combination with a 2¼" diameter of container 5 or with a 2½" diameter of container 5. This elongated configuration permits a single carrier 10 to be

used on a single applying machine 30 across an approximately .200" range of diameters of containers 5. This elongated configurations further permits the use of several carriers 10 having a constant pitch to be used on a single applying machine 30 across a wide range of diameters of containers 5.

Unlike typical container receiving apertures in the prior art, elongated apertures 20 are longer in a longitudinal direction than a diameter of container 5 to be engaged. As described above, elongated apertures 20 also differ from the container receiving apertures in the prior art in that elongated apertures 20 are approximately four to six times longer in the longitudinal direction than wide in a transverse direction. Prior art container receiving apertures generally have a longitudinal length (x) to transverse width (y) ratio (x/y) of 1.00 to 2.00. Therefore, typical prior art container receiving apertures are between 1 and 2 times longer in the longitudinal direction than wide in a transverse direction. Prior art container receiving apertures typically have longitudinal length to container diameter (d) ratios (x/d) between 0.80 to 1.00. Therefore, prior art container receiving apertures typically have a longitudinal length the same or less than the diameter of the container. By comparison, in one preferred embodiment of this invention, elongated apertures 20 have an x/y value of 4.90 and an x/d value of 1.05.

Additionally, carrier 10 is formed with a plurality of relief holes 25. Relief holes 25 are preferably positioned between adjacent longitudinal rows of elongated apertures 20. Relief holes 25 are preferably positioned in a single row in generally parallel alignment with respect to each adjacent relief hole 25. As shown in Fig. 3, relief

holes 25 may be parallel with respect to one another, though not necessarily.

In one preferred embodiment of this invention, longitudinal extremities 26 of relief holes 25 overlap end portions 22 of adjacent elongated apertures 20 in the longitudinal direction. If carrier 10 does not contain overlap area 28 between relief holes 25 and elongated apertures 20, high stress regions will form in areas immediately adjacent relief holes 25. Such high stress regions may result in failure of carrier 10 when assembled with containers 5. Overlap area 28 between relief holes 25 and elongated apertures 20 results in the effective formation of two distinct bands in the transverse region between the rows of elongated apertures 20.

In one preferred embodiment of this invention, shown in Figs. 3 and 4, center holes 27 are formed between each adjacent relief hole 25 in a single row in generally parallel alignment. Center holes 27 add flexibility to carrier 10 and further represent a savings in required material for each carrier 10.

As shown in Fig. 4, carrier 10 may also include features such as handle 12 for holding carrier 10. Additionally, features such as tear tabs 13 and perforations 14 may be included in carrier 10 to ease removal of containers 5 from carrier 10.

Each configuration of carrier 10 preferably accommodates a group of containers 5 having a uniform diameter within a range of diameters of approximately 0.2". Carrier 10 is preferably reconfigured for groups of container diameters in increments of approximately .2". Each different configuration of carrier 10 is preferably wider in a transverse direction of carrier 10, such as width 19 between outer edges of

elongated apertures 20. Regardless of diameter of container 5 or width of carrier 10, each configuration of carrier 10 preferably maintains an approximately constant longitudinal pitch 18 between each elongated aperture 20.

According to one preferred embodiment of this invention, a system for packaging multiple containers 5 includes moving carrier 10 through applying machine 30 wherein carrier 10 includes longitudinal pitch 18 between a center of each adjacent elongated aperture 20 having a first length. A side of view of carrier 10 having longitudinal pitch 18 is shown in Fig. 10 (thickness of carrier 10 is not to scale).

The plurality of containers 5 also moves through applying machine 30 and each container 5 is spaced apart from an adjacent container 5 by applying machine 30. The spacing between adjacent containers 5 as they enter applying machine 30 depends upon spacers positioned within applying machine 30. The spacers are set to accommodate the largest diameter container 5 to be used in applying machine 30.

Exiting applying machine 30, adjacent containers 5 are spaced apart at least a distance approximately equal to their respective maximum diameters 7. Maximum diameter 7 is often not uniform across container 5 because of the numerous contoured containers 5 currently utilized. Carrier 10 having the characteristics described in this Specification permits a tight configuration of package 15 regardless of contour of container 5, in part, because of the stretch of carrier 10 in the lateral direction.

As discussed in more detail below, carrier 10 is positioned over the plurality of containers 5 whereby each elongated aperture 20 engages with one of the containers

to form package 15 having a container pitch 16 between a center of adjacent containers 5 with a second length shorter than the first length. In practice, carrier 10 having elongated apertures 20 is reduced in overall longitudinal length subsequent to application to containers 5 and thus longitudinal pitch 18 is reduced in length to container pitch 16 after application. Fig. 11 shows container pitch 16 following application to containers 5.

According to one specific embodiment of this invention, the first length, or longitudinal pitch 18 of elongated apertures 20 in carrier 10, is approximately 3.0", prior to application to containers 5. In this specific embodiment, the second length, or container pitch 16 of elongated apertures 20 after application to containers is approximately 2.6". As a result, the first length prior to positioning over containers 5 is approximately 1.15 times greater than the second length after positioning over containers 5.

In practice, each group of containers 5, regardless of size, enters applying machine 30 at a first constant spacing or pitch, such as 3" between centers of adjacent containers 5. Following application of carrier 10 to containers 5, containers 5 exit applying machine at a second constant spacing or pitch, which is dependent upon the diameter of the specific containers used in the package and not necessarily equal to the first constant pitch, such as 2.6" between centers of adjacent containers 5. As a result, a single applying machine 30 and a single carrier 10 is all that is required to package a group of containers 5 having any number of maximum diameters 7, i.e., 2.6" diameter containers may be packaged with the same equipment as 3.0" diameter containers.

[illegible][illegible][illegible]

According to one preferred embodiment of this invention, shown in Figs. 8 and 9, each jaw pair 45 is movable between a closed position 53 and an open position 54 along an axis parallel to the axis of shaft 41. The closed position 53 comprises a relative position of jaw pair 45 when rods 47 are extended through supporting blocks 46 so that moveable jaw 48 is in a closest desired position relative to fixed jaw 49. The open position 54 comprises a relative position of jaw pair 45 when rods 47 are retracted through supporting blocks 46 so that moveable jaw 48 is in a farthest desired position relative to fixed jaw 49. In one preferred embodiment of this invention, jaw pairs 45 are moved between the open position 54 and the closed position 53 through the use of a cam roller 50 (Fig. 6) connected with respect to rods 47 and a cam (not shown) which is independently fixed with respect to drum 40. Therefore, the relative position of moveable jaw 48 with respect to fixed jaw 49 changes as drum 40 is rotated through a full 360° rotation.

Each jaw pair 45 is configured to grip carrier 10 with moveable jaw 48 and fixed jaw 49 engaged through each transverse pair of elongated apertures 20 in carrier 10. The circumferential spacing between adjacent jaw pairs 45 is preferably approximately equal to pitch 18 of carrier 10. The lateral spacing between moveable jaw 48 and fixed jaw 49 in the closed position 53 is preferably slightly less than width 19 between transverse pairs of elongated apertures 20. As shown in Fig. 7, carrier 10 is engaged with moveable jaw 48 and fixed jaw 49 of drum 40 prior to application to containers 5.

Drum 40 further comprises adjustment means 60 for predetermined and

precise adjustment of a distance between jaws, preferably moveable jaw 48 and fixed jaw 49, of each jaw pair 45 in the closed position 53. Preferably, adjustment means 60 adjusts adjustable block 51 and/or fixed jaw 49 of each jaw pair 45. In one preferred embodiment of this invention, adjustment means 60 adjusts each fixed jaw 49 of jaw pairs 45 simultaneously around the entire circumference of drum 40. In one preferred embodiment of this invention, in addition to the distance between the fixed jaw 49 and the moveable jaw 48, a width of guide plate 32 may be adjusted to correctly urge carrier 10 into engagement with drum 40.

In one preferred embodiment of this invention, drum 40 comprises stationary hub 63 and adjustable hub 65. Adjustment means 60 preferably comprises adjustable hub 65 journaled with respect to stationary hub 63 of drum 40. Preferably, adjustable hub 65 is slidably connected with respect to stationary hub 63 through a center hub assembly 70 around shaft 41 of drum 40. In addition, in one preferred embodiment of this invention, three adjuster guide assemblies 75 are positioned around drum 40 between stationary hub 63 and adjustable hub 65 at equal intervals. Preferably, adjuster guide assemblies 75 are synchronized using roller chain 82. Idler 80 is used to eliminate slack in roller chain 82. Adjustable hub 65, idler 80 and other adjustable components of applying machine 30 are preferably adjusted using one or more simple hand tools, such as a box wrench or open end wrench, to facilitate quick adjustment of drum 40. Therefore, when a smaller diameter container is packaged, a smaller size carrier 10 is required and adjustable hub 65 is readily and quickly adjustable.

As shown in Figs. 7-9, as jaw pairs 45 move with the rotation of drum 40 from a closed position 53 to an open position 54, elongated apertures 20 within carrier 10 stretch to accommodate container 5. Carrier 10 in a stretched condition is positioned over a plurality of containers 5 so that each elongated aperture 20 engages with one container 5. Upon engagement with containers 5, carrier 10 is released from jaw pair 45 and grips a perimeter of container 5. Finally, carrier 10 is cut into desired size to create package 15 such as a six-pack having two longitudinal rows and three transverse ranks.

If a group of second containers 5 having a different diameter is packaged, adjustment means 60 is adjusted to engage carrier 10 having a different width, such as width 19, but a common pitch 18 from every other carrier 10 used in combination with applying machine 30 according to this invention. Therefore, if a smaller diameter container is packaged and a smaller size carrier 10 is required, adjustable hub 65 is moved inwardly toward stationary hub 63. As a result, the distance between moveable jaw 48 and fixed jaw 49 in the closed position 53 is reduced and a new, smaller carrier 10 is engaged with jaw pairs 45 for application. Conversely, if a larger diameter container is packaged and a larger size carrier 10 is required, adjustable hub 65 is moved outwardly away from stationary hub 63. As a result, the distance between moveable jaw 48 and fixed jaw 49 in the closed position 53 is expanded and a new, larger carrier 10 is engaged with jaw pairs 45 for application.

A preferred range of container diameters accommodated by a single applying machine 30 according to this invention is an approximate 1" range, such as

between 2" and 3". Although this range of container diameters accounts for a majority of all containers currently available in multi-package format, other ranges of container diameters such as between 2½" and 3½" or between 3" and 4" are also contemplated by this invention.

While in the foregoing specification this invention has been described in relation to certain preferred embodiments thereof, and many details have been set forth for purposes of illustration, it will be apparent to those skilled in the art that the invention is susceptible to additional embodiments and that certain of the details described herein can be varied considerably without departing from the basic principles of the invention.

WE CLAIM:

1. A system for packaging multiple containers, the system comprising the steps of:

moving a carrier through an applying machine, the carrier constructed of flexible plastic having a plurality of elongated apertures aligned in transverse ranks, which elongated apertures are oriented in a longitudinal direction of the carrier and have a longitudinal pitch between a center of each adjacent elongated aperture, the longitudinal pitch having a first length;

moving a plurality of containers through the applying machine, each container of the plurality of containers having a maximum diameter having a second length shorter than the first length spaced apart from an adjacent container by the applying machine at the first length; and

positioning the carrier over the plurality of containers whereby each elongated aperture engages with one of the containers to form a package having a container pitch between a center of adjacent containers approximately equal to the second length.

2. The system of Claim 1 wherein the elongated apertures, in an unstressed condition prior to application to the plurality of containers, are approximately four to six times longer than wide.

3. The system of Claim 1 wherein the carrier further comprises a plurality of relief holes positioned between adjacent longitudinal rows of elongated apertures.
4. The system of Claim 3 wherein longitudinal extremities of the relief holes overlap end portions of adjacent elongated apertures in the longitudinal direction.
5. The system of Claim 1 wherein the first length is approximately 3.0”.
6. The system of Claim 5 wherein the second length is approximately 2.6”.
7. The system of Claim 1 wherein the first length is approximately 1.15 times greater than the second length.
8. The system of Claim 1 wherein an overall length of the carrier is reduced after the carrier is positioned over the plurality of containers to form a package.
9. An applying system for packaging multiple containers in a carrier, each container having a height and a maximum diameter, the applying system comprising: an applying machine accommodating a plurality of containers spaced at

intervals by the applying machine and the carrier having adjacent longitudinal rows of elongated apertures with a longitudinal pitch between each elongated aperture having a first length that is greater than the maximum diameter and, after application to the plurality of containers juxtaposed relative to one another, the container pitch between adjacent containers within the carrier is a second length, less than the first length and approximately equal to the maximum diameter.

10. The applying system of Claim 9 wherein the carrier further comprises a plurality of relief holes positioned between adjacent longitudinal rows of elongated apertures.

11. The system of Claim 9 wherein the first length is approximately 3.0".

12. The system of Claim 9 wherein the second length is approximately 2.6".

13. The system of Claim 9 wherein the first length is approximately 1.15 times greater than the second length.

14. A carrier for unitizing a plurality of containers, the carrier having an unstressed condition prior to application to the plurality of containers and a stressed

condition subsequent to application to the plurality of adjacent containers, each container of the plurality of adjacent containers having a maximum diameter, the carrier comprising:

a sheet of flexible plastic having a plurality of elongated apertures aligned in longitudinal rows and transverse ranks, which elongated apertures are oriented in a longitudinal direction of the carrier and in the unstressed condition have a longitudinal pitch between each adjacent elongated aperture, the longitudinal pitch having a first length greater than a distance between adjacent containers of the plurality of adjacent containers;

a plurality of relief holes positioned in the sheet, the relief holes positioned between adjacent longitudinal rows of elongated apertures; and

a container pitch between each adjacent elongated aperture when the carrier is in the stressed condition after application to the containers, the container pitch having a second length approximately equal to the maximum diameter and shorter than the first length.

15. The system of Claim 14 wherein the elongated apertures are approximately four to six times longer than wide.

16. The system of Claim 14 wherein longitudinal extremities of the relief holes overlap end portions of adjacent elongated apertures in the longitudinal direction.

17. The carrier of Claim 14 wherein the constant longitudinal pitch is maintained for a plurality of containers having a diameter within an approximate 1" range of diameters.

18. The carrier of Claim 14 wherein the plurality of containers each have a diameter within an approximate .200" range of diameters.

00370764760

ABSTRACT

A system for packaging multiple containers wherein a carrier is moved through an applying machine, the carrier constructed of flexible plastic having a plurality of elongated apertures aligned in transverse ranks, which elongated apertures are oriented in a longitudinal direction of the carrier and have a longitudinal pitch between a center of each adjacent elongated aperture, the longitudinal pitch having a first length. A plurality of containers are also moved through the applying machine, each container of the plurality of containers spaced apart from an adjacent container by the applying machine. The carrier is subsequently positioned over the plurality of containers whereby each elongated aperture engages with one of the containers to form a package having a container pitch between a center of adjacent containers with a second length shorter than the first length.




FIG. 1 PRIOR ART




FIG. 2




FIG. 3




FIG. 4

009111 04E4F260




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 11

COMBINED DECLARATION, POWER OF ATTORNEY AND PETITION

We, the inventors,

1. Name: William N. WEAVER
Residence: Northbrook, Illinois
Post Office Address: 2625 Quail Lane
Northbrook, Illinois 60062
Citizenship: United States of America
2. Name: Robert E. UNGAR
Residence: Des Plaines, Illinois
Post Office Address: 9358 Margail
Des Plaines, Illinois 60016
Citizenship: United States of America
3. Name: Lonnie R. SEYMOUR
Residence: Naperville, Illinois
Post Office Address: 223 Oxford Court
Naperville, Illinois 60540
Citizenship: United States of America

declare that we have reviewed and understand the contents of the attached specification and claims and we verily believe that we are the original, first and joint inventors or discoverers of the invention or discovery in

SYSTEM AND APPARATUS FOR PACKAGING CONTAINERS

COMBINED DECLARATION, POWER

described and claimed in the attached specification; that we do not know and do not believe that this invention was ever known or used in the United States before our invention or discovery thereof; that to the best of our knowledge and belief the invention has not been in public use or on sale in the United States more than one year prior to our application, or patented or made the subject of an inventors' certificate in any foreign country prior to the date of our application on an application filed by ourselves or our legal representatives or assigns more than twelve months prior to our application in this country; that we acknowledge our duty to disclose information of which we are aware which is material to the examination of this application in accordance with 37 C.F.R. 1.56(a); and that no application for patent or inventors' certificate on this invention or discovery has been filed by us or our legal representatives or assigns in any country foreign to the United States, except as follows:

None

POWER OF ATTORNEY

We hereby appoint the following attorneys to prosecute this application and transact all business in the United States Patent and Trademark Office connected therewith:

22,617	Thomas W. Speckman	Registration	No.
33,295	Douglas H. Pauley	Registration	No.
32,772	Maxwell J. Petersen	Registration	No.
31,631	Charles C. Kinne	Registration	No.
34,817	Mark E. Fejer	Registration	No.
	Nick C. Kottis	Registration No. 31,974	
38,736	Kevin D. Erickson	Registration	No.
32,799	Roland W. Norris	Registration	No.
40,924	Melanie I. Rauch	Registration	No.
42,769	Eric T. Krischke	Registration	No.
	Mark W. Croll	Registration No. 31,098	

COMBINED DECLARATION, POWER

Lisa Soltis
40,623
Registration No.

SEND CORRESPONDENCE TO: DIRECT
TELEPHONE CALLS TO:

Kevin D. Erickson
Pauley Petersen Kinne & Fejer
2800 West Higgins Road
Suite 365
Hoffman Estates, Illinois 60195
(847) 490-1400
FAX (847) 490-1403

Kevin D. Erickson
(847) 490-1400
(847) 490-1403 - Fax

PETITION

Wherefore we Pray that Letters Patent be granted to us for the invention or discovery described and claimed in the attached specification and claims, and we hereby subscribe our names to the attached specification and claims, Declaration, Power of Attorney and this Petition.

DECLARATION

The undersigned further declare that all statements made herein of their knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

William D. Weaver 11/15/00
Date William N.
WEAVER

Robert E. Ungar 11/15/00
Date Robert E.
UNGAR

Lonnie R. Seymour 11/15/00
Date Lonnie R.
SEYMOUR